


Primo 19 ST BMP

Anchor point for steel surfaces

DIN EN
795



Technical specifications		
Material	stainless steel (V2A)	stainless steel (V2A)
Pipe diameter	Ø 20 mm	Ø 20 mm
Base plate	100 x 70 x 5 mm	100 x 70 x 5 mm
Number of users	max. 3 persons	max. 3 persons
Steel strength	min. S235	min. S235
Steel thickness	3 - 6 mm	6 - 12 mm
Self-drilling screws (12 pcs.)	EJOT JT3-6-5,5 x 35	EJOT JT3-12-5,5 x 40

Version	Art.-Nr.	Height	Roof structure
Primo 19 ST BMP/30	CH109300	300 mm	0 - 100 mm
Primo 19 ST BMP/40	CH109400	400 mm	0 - 200 mm
Primo 19 ST BMP/50	CH109500	500 mm	0 - 300 mm
Primo 19 ST BMP/60	CH109600	600 mm	0 - 400 mm
Primo 19 ST BMP/70	CH109700	700 mm	0 - 500 mm
Primo 19 ST BMP/80	CH109800	800 mm	100 - 600 mm
Primo 19 ST BMP/90	CH109900	900 mm	200 - 700 mm
Primo 19 ST BMP/100	CH1099100	1000 mm	300 - 800 mm