


Primo 3 SP-HO

Anchor point for prestressed concrete hollow ceilings



Technical specifications		
Material	stainless steel (V2A)	stainless steel (V2A)
Pipe diameter	Ø 20 mm	Ø 20 mm
Base plate	220 x 220 x 5 mm	220 x 220 x 5 mm
Number of users	max. 3 persons	max. 3 persons
Concrete strength	min. C45 / 55	min. C45 / 55
Web thickness	min. 27,5 mm	min. 27,5 mm
Edge distance	min. 300 mm	min. 300 mm
Drill hole diameter	Ø 16 mm	Ø 16 mm
Drill hole depth	65 mm	60 mm
Hollow ceiling anchor (4 pcs.)	FHY M10 A4	MKT EASY M10

Version	Art.-Nr.	Height	Roof structure
Primo 3 SP-HO/30	133300	300 mm	0 - 100 mm
Primo 3 SP-HO/40	133400	400 mm	0 - 200 mm
Primo 3 SP-HO/50	133500	500 mm	0 - 300 mm
Primo 3 SP-HO/60	133600	600 mm	0 - 400 mm
Primo 3 SP-HO/70	133700	700 mm	0 - 500 mm
Primo 3 SP-HO/80	133800	800 mm	100 - 600 mm
Primo 3 SP-HO/80	133900	900 mm	200 - 700 mm
Primo 3 SP-HO/100	1339100	1000 mm	300 - 800 mm