


Primo 3 SP-HO BMP

Anchor point for prestressed concrete

DIN EN
795



Technical specifications	
Material	Stainless steel (V2A)
Pipe diameter	Ø 20 mm
Base plate	220 x 220 x 5 mm
Number of users	max. 3 persons
Concrete strength	min. C45 / 55
Web thickness	min. 27,5 mm
Edge distance	min. 300 mm
Drilling hole diameter	Ø 16 mm
Drilling hole depth	65 mm
Hollow ceiling anchors (4 pcs.)	FHY M10 A4

Version	Art. no.	Height	Roof structure
Primo 3 SP-HO BMP/30	CH133300	300 mm	0 - 100 mm
Primo 3 SP-HO BMP/40	CH133400	400 mm	0 - 200 mm
Primo 3 SP-HO BMP/50	CH133500	500 mm	0 - 300 mm
Primo 3 SP-HO BMP/60	CH133600	600 mm	0 - 400 mm
Primo 3 SP-HO BMP/70	CH133700	700 mm	0 - 500 mm
Primo 3 SP-HO BMP/80	CH133800	800 mm	100 - 600 mm
Primo 3 SP-HO BMP/80	CH133900	900 mm	200 - 700 mm
Primo 3 SP-HO BMP/100	CH1339100	1000 mm	300 - 800 mm