

Primo 60 AD - 10

Cable access technology for concrete surfaces



Technical specifications	
Material	Stainless steel (V2A)
Number of users als single anchor point	max. 3 persons
Number of users als cable access technology	max. 1 person
Concrete strength	min. C20 / 25
Concrete thickness	min. 100 mm
Edge distance	min. 425 mm
Drilling hole diameter	Ø 12 mm
Drilling hole depth	70 mm
Installation	Wall, ceiling, overhead

Version	Art. no.	Height	Bolt anchors
Primo 60 AD-10/20	6010200	200 mm	FAZ II 12/10 R
Primo 60 AD-10/30	6010300	300 mm	FAZ II 12/10 R
Primo 60 AD-10/40	6010400	400 mm	FAZ II 12/10 R
Primo 60 AD-10/50	6010500	500 mm	FAZ II 12/10 R
Primo 60 AD-10/60	6010600	600 mm	FAZ II 12/10 R
Primo 60 AD-10/70	6010700	700 mm	FAZ II 12/10 R
Primo 60 AD-10/80	6010800	800 mm	FAZ II 12/10 R
Primo 60 AD-10/90	6010900	900 mm	FAZ II 12/10 R
Primo 60 AD-10/100	6010100	1000 mm	FAZ II 12/10 R