

Primo 6 AD BMP

Anchor point for concrete surfaces

DIN EN
795



Technical specifications	
Material	Stainless steel (V2A)
Pipe diameter	Ø 20 mm
Number of users	max. 2 persons
Concrete strength	min. C20 / 25
Concrete thickness	min. 140 mm
Edge distance	min. 300 mm
Drilling hole diameter	Ø 16 mm
Drilling hole depth	125 mm
Bolt anchor (1 pcs.)	FAZ II 16/25 R or MKT BZ3 M16x145/0-45 A4
Installation	Single-hole installation

Version	Art. no.	Height	Roof structure
Primo 6 AD BMP/30	CH106300	300 mm	0 - 100 mm
Primo 6 AD BMP/40	CH106400	400 mm	0 - 200 mm
Primo 6 AD BMP/50	CH106500	500 mm	0 - 300 mm
Primo 6 AD BMP/60	CH106600	600 mm	0 - 400 mm
Primo 6 AD BMP/70	CH106700	700 mm	0 - 500 mm
Primo 6 AD BMP/80	CH106800	800 mm	100 - 600 mm
Primo 6 AD BMP/90	CH106900	900 mm	200 - 700 mm
Primo 6 AD BMP/100	CH1069100	1000 mm	300 - 800 mm