

Guardrail TB

Guardrail for skylight domes

DIN EN 13374:A

Technical specifications	
Material	Aluminium
Available post height	1200 mm
Height adjustability	0 – 200 mm
Diameter of the hand and knee rails	Ø 40 mm
Length of the base outrigger	500 mm
Lightning protection tested	in accordance with DIN EN 62561-1

Installation	
Fastening	Load-bearing
Plastic weights	25 kg each

Norms	DIN EN 13374:A
Roof inclination	max. 10°
Area between the rails	max. 470 mm
Axle distance of guardrail posts	max. 2500 mm
Toe board required for an parapet height	< 180 mm



Guardrail TB

Guardrail for skylight domes

DIN EN 13374:A

Version	Article no.	Width	Length
Guardrail TB/10	961000	1000 mm	1000 mm
Guardrail TB/15	961100	1500 mm	1500 mm
Guardrail TB/20	961200	2000 mm	2000 mm
Guardrail TB/25	961300	2500 mm	2500 mm
Guardrail TB with door/10	961400	1000 mm	1000 mm
Guardrail TB with door/15	961500	1500 mm	1500 mm
Guardrail TB with door/20	961600	2000 mm	2000 mm
Guardrail TB with door/25	961700	2500 mm	2500 mm