Primo 2 SP-HO BMP

Anchor point for hollow-core prestressed concrete



DIN EN 795

Technical specifications	
Material	Stainless steel (V2A)
Pipe diameter	Ø 20 mm
Base plate	100 x 200 x 5 mm

Installation	
Number of users	max. 3 persons
Concrete strength class	min. C45/55
Web thickness	min. 27,5 mm
Edge distance	min. 300 mm
Drill hole diameter	Ø 16 mm
Drill hole depth	min. 65 mm
Hollow-ceiling anchors (2 pcs.)	FHY M10 R

Version	Article no.	Height	Roof build-up
Primo 2 SP-HO BMP/30	127300	300 mm	≤ 100 mm
Primo 2 SP-HO BMP/40	127400	400 mm	≤ 200 mm
Primo 2 SP-HO BMP/50	127500	500 mm	≤ 300 mm
Primo 2 SP-HO BMP/60	127600	600 mm	≤ 400 mm
Primo 2 SP-HO BMP/70	127700	700 mm	≤ 500 mm
Primo 2 SP-HO BMP/80	127800	800 mm	100 – 600 mm
Primo 2 SP-HO BMP/90	127900	900 mm	200 – 700 mm
Primo 2 SP-HO BMP/100	1279100	1000 mm	300 - 800 mm