Primo 60 AD-10

Rope access system for concrete substrates



aBG

Technical specifications	
Material	Stainless steel (V2A)
Pipe diameter	refer to the static calculation
Base plate	refer to the static calculation

Installation	Bolt anchors	Injection mortar
Number of users	max. 3 persons	max. 3 persons
Rope access system	max. 1 person	max. 1 person
Concrete strength class	min. C20/25	min. C20/25
Concrete thickness	min. 100 mm	min. 100 mm
Edge distance	refer to the static calculation	refer to the static calculation
Drill hole diameter	refer to the static calculation	refer to the static calculation
Drill hole depth	refer to the static calculation	refer to the static calculation
Bolt anchors (4 or 8 pcs.)	refer to the static calculation	-
Special mortar	-	refer to the static calculation
Anchor rods (4 or 8 pcs.)	-	refer to the static calculation
Nuts (4 or 8 pcs.)	-	refer to the static calculation
Washers (4 or 8 pcs.)	-	refer to the static calculation

Primo 60 AD-10

Rope access system for concrete substrates



aBG

Version	Article no.	Height
Primo 60 AD-10/20	6010200	200 mm
Primo 60 AD-10/30	6010300	300 mm
Primo 60 AD-10/40	6010400	400 mm
Primo 60 AD-10/50	6010500	500 mm
Primo 60 AD-10/60	6010600	600 mm
Primo 60 AD-10/70	6010700	700 mm
Primo 60 AD-10/80	6010800	800 mm
Primo 60 AD-10/90	6010900	900 mm
Primo 60 AD-10/100	6010100	1000 mm